TORO POLY MANIFOLDS

Toro Polypropylene Manifolds are ideal for residential, landscape and commercial applications with 25mm Solenoid Valves.

FEATURES & BENEFITS

Sealing Threads
Tapered sealing threads on the BSPM fittings ensure a tight seal even if the O-Ring is not reached.

Set O-Rings
Pre-installed O-Ring ensures a tight seal between fittings and valves.

Full Range
Manifolds available in 1, 2, 3 or 4 Outlet options, and a wide range of fittings including Elbows, End Cap and Nipple.

Easy to Install
With the Union fittings, threading valves or fittings into the Manifolds is simple and can be done in tight spaces.

SPECIFICATIONS

Applications
Ideal for landscape or light commercial applications for use within valve boxes for connecting valves to the irrigation system

Technical Data
Operating Pressure: up to 1034 kPa

Suits: 25 mm Female Inlet Irrigation Valves

Ordering Information	
Code	**Description**
TPM-EC	Poly Manifold End Cap 25 mm
TPM-N	Poly Manifold Nipple 25 mm
TPM-C	Poly Manifold Union Coupling 25 mm
TPM-ME	Poly Manifold BSPM / Union Elbow 25 mm
TPM-UE	Poly Manifold Union / Union Elbow 25 mm
TPM-1P	Poly Manifold Single Outlet 25 mm
TPM-2P	Poly Manifold Two Outlet 25 mm
TPM-3P	Poly Manifold Three Outlet 25 mm
TPM-4P	Poly Manifold Four Outlet 25 mm